

APPLICATION FOR UNITED STATES LETTERS PATENT

HIGH-SPEED SHEAR FOR TRANSVERSELY CUTTING ROLLED STRIP

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a high-speed shear with a knife, particularly a chisel-type knife with a knife edge, arranged on at least one of two oppositely arranged drums, wherein the knife can be accelerated to the feeding speed of the rolled strip and the drums can be adjusted relative to each other for carrying out a cut. At least one drive unit provided for the drums serves to accelerate the drums to the speed of the rolled strip to be cut and at least one of the drums may be provided with a separately controllable adjusting device.

2. Description of the Related Art

In the manufacture of hot-rolled wide strip, the endless rolling method is used more and more. The material used is produced by welding preliminary strips or in casting machines. However, hot-rolled wide strip is also manufactured by using a semi-endless rolling method in which the material used may have the length of several preliminary strips which may be stored intermediately on roller tables, roller-hearth furnaces or in coil boxes.

After the hot-rolling procedure, the finished strip must be cut to the strip lengths corresponding to the required coil weights. The cut should be carried out in a continuous operation, i.e., at rolling speed. Accordingly, the cut must be carried out at the speeds of trains for hot-rolling wide strip which are conventional today in the range of 5 m/sec. to 30 m/sec., preferably 10 m/sec. to 20 m/sec. The strip thicknesses are between 0.5 mm to 30 mm, preferably between 0.6 mm to 1.5 mm.

Rotary shears or guillotine shears which are conventional in the art and serve to cut hot-rolled wide strip, are not designed for such high strip speeds. However, flying shears which are used following cold-rolling tandem trains usually operate today only at strip speeds of about 6 m/sec; in these type of shears there is also a demand for significantly higher speeds.

At such high strip speeds, it is no longer possible to economically carry out the conventional cutting procedures in which the knife drum is accelerated to a strip speed of up to 30 m/sec. for carrying out the cut and in which the knife drum must subsequently be decelerated again.

In order to eliminate these difficulties, it has already been proposed to control the acceleration of the knife drum to

strip speed or the operation of the knife drum at strip speed separate of the movement to be carried out perpendicularly of the strip and to provide for at least one of the drums a separately controllable adjusting device.

In this connection, it is possible to provide one of the drums with a knife and the other drum with an anvil or a surface portion acting as an anvil which interacts with the knife.

However, when the shear has this configuration, a safe and exact cut can only be ensured if the cutting gap between the knife cutting edge and the anvil or the surface portion of the counter-drum is zero. If this is not the case, for example, if the knife has an excess length, the knife and the anvil may be overloaded until they are destroyed, or when the knife has an insufficient length the cut remains incomplete.

However, due to one or more interacting variables including thermal extension, wear, elastic behavior of the adjusting devices, acceleration forces, finishing tolerances, etc. the adjustment of the cutting gap to "zero" cannot be achieved with the required certainty. Therefore, it is necessary for a certain and reliable cutting of the strip that the knife protrudes from the cutting circle. However, this protrusion leads to a rapid

1. The first group of people who are interested in the study of the history of the United States are the people who are interested in the history of the United States. They are interested in the history of the United States because they want to know more about the United States. They want to know more about the United States because they want to know more about the United States.

SUMMARY OF THE INVENTION

Therefore, starting from the prior art discussed above, it is the primary object of the present invention to further develop a high-speed shear for cutting hot-rolled and cold-rolled strip while avoiding the aforementioned difficulties and technical limits in such a way that exact cuts are safely ensured at strip speeds of up to 30 m/sec., even in the case of minimum strip thicknesses. This is to be achieved while avoiding an overloading of knife, and/or of the surface portion of the counter-drum, of the adjusting mechanisms and the bearings of the drum, and/or to avoid an incomplete cut.

In accordance with the present invention, in a high-speed shear of the type described above, the chisel-type knife of the knife drum is mounted so as to protrude from the cutting circle towards the anvil or the surface portion of the second drum acting as an anvil and to mount the chisel-type knife of the knife drum so as to be resiliently supported against a predetermined restoring force.

In accordance with a further development of the invention, the chisel-type knife is mounted so as to be resiliently supportive in a radial guide means of the knife drum. Instead of

the radial guide means it can also be provided that the chisel-type knife is mounted so as to be resiliently supported on a link, wherein the point of rotation of the link is located on the knife drum.

In accordance with an alternative embodiment of the present invention, the chisel-type knife is clamped non-resiliently in the knife drum and the adjusting device which supports the knife drum with its bearing is mounted so as to be resiliently supported relative to a predeterminable restoring force.

Both technical solutions achieve the same result, namely the knife which initially protrudes out of the cutting circle can yield during the cutting process when meeting the anvil, or the surface of the second drum serving as an anvil, to such an extent that an impermissible increase of the cutting forces and, thus, wear phenomena at all structural components of the cutting elements or adjusting device and including the bearings of the drum can be safely avoided.

In accordance with an embodiment of the invention, one of the drums is provided with a chisel-type knife and the other drum is equipped with an anvil interacting with the knife. However, alternatively it is also possible that one of the drums is

equipped with a chisel-type knife which interacts with a surface portion of the second drum which acts as an anvil.

The present invention provides the result that the chisel-type knife meets the strip as the drum rotates, the knife cuts the strip and makes contact with the anvil or the surface portion of the counter-drum acting as an anvil and subsequently yields or resiliently moves back.

The interaction between the chisel-type knife and the anvil drum provides the advantage that the synchronization of the circumferential speeds of both drums does not have to be particularly precise. On the contrary, in the case of a difference of the circumferential speeds of the chisel-type knife and the anvil drum, the entire circumference of the anvil drum can be utilized in the interaction of the knife so that a wear distribution is achieved and the availability of the shear is favorably improved.

Consequently, the principle described above is especially suitable for highest strip speeds in the rough operating conditions of hot rolling mills.

The various features of novelty which characterize the invention are pointed out with particularity in the claims annexed to and forming a part of the disclosure. For a better understanding of the invention, its operating advantages, specific objects attained by its use, reference should be had to the drawing and descriptive matter in which there are illustrated and described preferred embodiments of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2

BRIEF DESCRIPTION OF THE DRAWING

In the drawing:

Fig. 1 is a side view, partially in section, showing a knife drum interacting with an anvil drum;

Fig. 2 is a side view, partially in section, of another embodiment with a knife drum interacting with an anvil drum;

Fig. 3 is a sectional view, on a larger scale, perpendicularly of the axis of rotation of a knife drum with a resiliently supported chisel-type knife;

Fig. 4 is a sectional view, also on a larger scale, of a knife drum with a pneumatically/hydraulically supported chisel-type knife interacting with an anvil drum;

Fig. 5 is a side view of an adjusting device for the chisel-type knife and the anvil drum with resilient support of an adjusting beam;

Fig. 6 is a side view, partially in section, of a chisel-type knife of a knife drum supported by a plurality of resilient support elements;

Fig. 7 is a schematic illustration of the knife drum and the anvil drum with an elastic chisel-type knife, wherein the drums are deformed by the load; and

Fig. 8 is a schematic illustration similar to Fig. 7, showing a segmented chisel-type knife.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 of the drawing shows a flying high-speed shear with knife drum 6 and an anvil drum 7 which interacts with the knife drum 6 for cutting a rolled strip 4. The two drums 6, 7 can be accelerated by means of a drive device, not shown, to the feeding speed of the rolled strip 4 to be cut and are adjustable relative to each other for performing a cut by means of an adjusting device 36 which is known in the art and is illustrated in Fig. 5. By means of such an adjusting device the two drums 6, 7 are accelerated independently of the adjusting procedure for carrying out a cut to a circumferential speed which corresponds to the feeding speed of the strip 4 to be cut and the two drums are maintained during the further duration of operation at this circumferential speed, while the adjustment for carrying out the cut is reversed immediately after a cut has been carried out into an open neutral position, so that a predetermined length of the strip can pass through the shear uncut.

In accordance with the present invention, the chisel-type knife 1 of the knife drum 6 is mounted so as to protrude out of the cutting circle 40 toward an anvil 24 shown in Fig. 5 or a surface portion of the drum 7 acting as an anvil and so as to be resiliently supported with a predeterminable restoring force

against a steel spring stack 12. The chisel-type knife 1 may be resiliently supported in a radial guide means 9 of the knife drum 6. In the embodiment of the knife support according to Fig. 1 the radial guide means 9 receives the chisel-type knife 1 so as to be guided with its shaft 11 in radial direction. The shaft 11 has a flange 10 against which the steel spring stack 12 rests, so that the chisel-type knife 1 is resiliently supported in its protruding cutting position with a predetermined restoring force. The flange 10 is held by a locking element 8 in radial direction, wherein the locking element 8 is secured to the drum 6 by means of screws 20. In this manner, during the cutting process after the rolled strip 4 has been cut the chisel-type knife can be resiliently forced back against the force of the spring in the direction toward the drum center to such an extent that damage to the knife cutting edge 3 or the surface portion of the anvil drum 7 is avoided. The anvil drum 7 may be of relatively soft material in order to protect the chisel-type knife 1.

In Figs. 1 and 2, the separately controllable adjusting device 36 is schematically indicated as a double arrow. The configuration of such an adjusting device is known in the art. Fig. 5 shows as an example an adjusting device 36 with links 25, 26 actuated by eccentric adjusting members 22, 23. Fig. 5 further shows an alternative embodiment of the invention in which

the chisel-type knife 2 is non-resiliently mounted in the knife drum 6 and the adjusting device 36 receiving the knife drum 6 with its bearing is mounted so as to be resiliently supported with a predeterminable restoring force against a spring strut 29.

In this embodiment, the knife 2 can also resiliently yield out of the cutting circle 40 against the anvil 24 when a predetermined peak load has been reached, wherein the link 25 is lifted by a corresponding extent against the force of the spring 30 in order to avoid an overloading of knife 2, anvil 24 and all other structural components including the bearings of the drums 6 and 7.

Fig. 3 shows the embodiment of the invention according to Fig. 1 on a larger scale. Equal elements are provided with the same reference numerals. Fig. 3 shows that the knife cutting edge 3 protrudes by a dimension \bar{U} from the circular circumference of the knife drum 6. In this embodiment, in which the knife shaft 11 is supported resiliently against the steel spring stack 12, the knife shaft 11 is extended upwardly in the form of a pressure rod 16. The pressure plate 15 serves to limit the displacement distance which is schematically indicated by a double arrow in the knife shaft 11. The pressure rod 16 is

screwed into a screw connection 17 which permits adjustment of the pretensioning force of the steel spring stack 12.

In accordance with a modified embodiment of the present invention as compared to that shown in Figs. 1 and 3, Figs. 2 and 4 show an embodiment in which the chisel-type knife 1 is mounted in the radial guide means 9 supported against a gas pressure spring 21. The gas pressure spring 21 transmits the pressure to the piston 13 which is guided in the cylinder 14 and which, in turn, transmits the predetermined cutting force of the chisel-type knife 1 through the flange 10 and the knife shaft 11 to the knife cutting edge 3. In principle, the different spring elements 12 and 21 are means which act in the same manner and which can be selected by those skilled in the art as desired.

The enlarged illustration of Fig. 4 further shows a closing fitting 19 of the pressure space 18 through which the gas pressure or the loading of the pressure space 18 with pressurized gas can be adjusted and varied. The lower pressure space can optionally be charged with a hydraulic liquid 35 or with pressurized gas. The operation of the devices shown in Figs. 2 and 4 are otherwise the same in principle and meet the object described above.

The embodiments illustrated in the drawing are only possible examples. Other embodiments for mounting the chisel-type knife in a resilient manner may include elastomers as they are known for spring-like support and damping of moving masses, combinations of gaseous media and hydraulic media, as they are known in piston reservoirs in hydraulic plants, etc..

Fig. 5 schematically shows the alternative embodiment of the invention which has already been discussed above. The knife drum 6 has a chisel-type knife 2 which is mounted in a non-resilient manner and which interacts with the anvil 24 of the anvil drum 7 for cutting the rolled strip 4 with a severing cut when the adjusting device 36 is appropriately adjusted. Since the eccentric adjusting members 22, 23 of the adjusting device 36 describe an unchanging eccentric path, a protruding dimension \bar{U} of the chisel-type knife 2 relative to the anvil 24 would be required for achieving a cutting gap of the size zero. This would inevitably lead to a spontaneous increase of the force acting between the knife cutting edge 3 and the anvil 24 and, thus, the entire adjusting device 36 including the bearings of the eccentric members, the drums and the hinges 27, 28 at the links 25, 26. For example, in order to prevent an overloading of all structural elements in accordance with the teaching of the present invention by supporting the chisel-type knife against a

spring element with a predeterminable restoring force, the link 25 is supported with its hinge 28 resiliently against the spiral spring 30 which is shown as an example. The spring strut 29 serves to effect a linear guidance in the guide element 32 and the movement of the spring strut 29 is limited downwardly by the adjusting screw 32.

For putting into effect the resilient support of the chisel-type knife 1 in the cutting position in accordance with the teaching of the present invention, it is not absolutely required that the elements exerting the restoring force are present directly in the knife drum 6. Rather, it is within the discretion of those skilled in the art to select equivalent available means in the form of a suitable spring element to be integrated also in other components of the high-speed shear, such as, for example, in the adjusting device according to Fig. 5. In principle, it would also be possible to mount other structural components of the adjusting device so as to be resiliently supported and to use for this purpose, for example, the bearings of the drums 6, 7 or the eccentric adjusting members 22, 23 or the links 27, 28. It must be ensured in all cases that the forces acting between the chisel-type knife 2 and the anvil 24 do not exceed a predetermined maximum.

Fig. 6 shows another alternative embodiment of the present invention. A chisel-type knife 1 is mounted in the knife drum 6 in a radial guide means 9. For achieving the necessary cutting force the chisel-type knife 1 is resiliently mounted in radial direction by means of a row of plate spring stacks 12'. By means of an adjusting mechanism 33 using a number of clamped wedges with inclined wedge surfaces, the spring pretension and, thus, the spring travel distance and the spring progression can be changed by means of the adjusting distance 34. The drums 6 are supported in loose bearings 37, 38 on both sides by means of cylindrical roller bodies. In order to achieve a uniform wear, the knife drum 6 can be moved back and forth in axial direction with a slight axial degree of freedom.

In order to achieve a constant cutting force over the strip width the chisel-type knife 1 shown in Fig. 7 has a low bending stiffness. Alternatively, as shown in Fig. 8, the knife may be segmented into knife segments 1'. This makes it possible to adapt the chisel-type knife to the deformation of the knife drum 6 and the anvil drum 7. In order to illustrate this principle, the deformations of the knife drum 6 and the anvil drum 7 are shown significantly exaggerated.

The resilient support 12 in the form of segments can also be provided on the anvil drum 7 instead of on the knife 1. The principle of the knife resiliently supported by segments can also be utilized, for example, as overload protection in other shears which do not have chisel-type knives but "real" cutting knives.

The present invention improves in an optimum manner a high-speed shear to make it possible to achieve clean cuts without overloading structural components of the shear, especially at speeds of the rolled strip to be cut of up to 30 m/sec. to

While specific embodiments of the invention have been shown and described in detail to illustrate the inventive principles, it will be understood that the invention may be embodied otherwise without departing from such principles.